

全方位門禁讀頭

多款門禁讀頭，提供全方位的運用



多輸出格式

AR-101U/AR-725K/AR-725U/
AR-721U/AR-331K/AR-331U/AR-661U



雙頻

AR-101U



體積小

AR-101U/AR-721U



觸碰式背光面板

AR-725K/AR-725U/AR-331K/AR-331U



金屬材質機身

AR-331K/AR-331U



防塵/防水等級

IP55: AR-725K/AR-725U
IP56: AR-721U/AR-725U/
AR-331K/AR-331U/AR-661U



全方位門禁讀頭

多款門禁讀頭，提供全方位的運用

讀頭
AR-101U



長距離讀頭
AR-661U



讀頭
AR-721U



按鍵型讀頭
AR-721K



感應頻率	13.56MHz	13.56MHz+125kHz	125kHz	125kHz	13.56MHz	125kHz	13.56MHz
工作電壓	9-24VDC		12-16VDC	9-24VDC		9-24VDC	10-24VDC
資料傳輸標準	EM Standard	·ISO14443A (可選購) ·MIFARE ·DESFire	EM Standard	EM Standard	·ISO14443A (可選購) ·ISO15693 ·ISO7816 ·DESFire ·PSAM ·NFC	EM Standard	·ISO14443A (可選購) ·ISO15693 ·DESFire ·PSAM ·NFC
感應距離 <small>(取決於TAG或卡片)</small>	2-5cm	1-3cm	33-60cm	6-12cm	3-8cm	10-18cm	3-8cm
讀/寫功能	Read Only	Read/Write	Read Only	Read Only	Read/Write	Read Only	Read/Write
消耗功率	<1W		<3W	<1W		<1W	
通訊介面	Wiegand24/36, ABA-II, ASYNC		Wiegand, ABA-II, ASYNC	Wiegand, ABA-II, ASYNC		Wiegand, ABA-II, ASYNC	
傳輸速率	9600 bps(N,8,1)		9600 bps(N,8,1)	9600 bps(N,8,1)		9600 bps(N,8,1)	
環境溫度	-20 °C to +60 °C		-20 °C to +60 °C	-20 °C to +60 °C		-20 °C to +60 °C	
按鍵	No		No	No		Yes	
指示器	1組雙色LED+1組蜂鳴器		3組LED & 1組蜂鳴器	1組雙色LED+1組蜂鳴器		1組雙色LED+1組蜂鳴器	
防水指數	NO		IP56	IP56(選購)		No	
外殼材質	ABS		ABS	ABS		ABS	
顏色	深灰		深灰	標準: 黑/灰/銀 選購: 白/藍/綠/黃/橘/紅		深灰/銀	
外型尺寸(mm)	37(L)X37(W)X31(H)		228(L)X228(W)X38(H)	81(L)X43(W)X18(H)		111(L)X77(W)X26(H)	
重量(g)	26±10		1000±50	40±10		90±10	

金屬讀頭
AR-331U



金屬按鍵讀頭
AR-331K



讀頭
AR-725U
AR-725U-M



按鍵型讀頭
(觸碰式背光)
AR-725K
AR-725K-M



感應頻率	125kHz	13.56MHz	125kHz	13.56MHz	125kHz	13.56MHz	125kHz	13.56MHz
工作電壓	9-24VDC		9-24VDC		9-24VDC		9-24VDC	
資料傳輸標準	EM Standard	·ISO14443A (可選購) ·ISO15693 ·DESFire ·PSAM ·NFC	EM Standard	·ISO14443A (可選購) ·ISO15693 ·DESFire ·PSAM ·NFC	EM Standard	·ISO14443A (可選購) ·ISO15693 ·DESFire ·PSAM ·NFC	EM Standard	·ISO14443A (可選購) ·ISO15693 ·DESFire ·PSAM ·NFC
感應距離 <small>(取決於TAG或卡片)</small>	3-7cm	1-3cm	3-7cm	1-3cm	5-15cm(725U) 5-8cm(725U-M)	3-8cm(725U) 3-5cm(725U-M)	5-15cm(725K) 5-8cm(725K-M)	3-8cm(725K) 3-5cm(725K-M)
讀/寫功能	Read Only	Read/Write	Read Only	Read/Write	Read Only	Read/Write	Read Only	Read/Write
消耗功率	<1W		<1W		<1W		<1W	
通訊介面	Wiegand, ABA-II, ASYNC		Wiegand, ABA-II, ASYNC		Wiegand, ABA-II, ASYNC		Wiegand, ABA-II, ASYNC	
傳輸速率	9600 bps(N,8,1)		9600 bps(N,8,1)		9600 bps(N,8,1)		9600 bps(N,8,1)	
環境溫度	-20 °C to +60 °C		-20 °C to +60 °C		-20 °C to +60 °C		-20 °C to +60 °C	
按鍵	No		Illuminated Touch-panel		No		Illuminated Touch-panel	
指示器	2組LED+1組蜂鳴器		2組LED+1組蜂鳴器		3組LED+1組蜂鳴器		1組雙色LED+1組蜂鳴器	
防水指數	IP56		IP56		IP55 / IP56(選購)		IP55	
外殼材質	鋅合金		鋅合金		鋅合金+PC(725U-M) / PC(725U)		鋅合金+PC(725K-M) / PC(725K)	
顏色	Chrome		Chrome		標準: 黑/灰/銀 選購: 白/藍/綠/黃/橘/紅		標準: 黑/灰/銀 選購: 白/藍/綠/黃/橘/紅	
外型尺寸(mm)	154(L)X51(W)X21(H)		154(L)X51(W)X21(H)		79(L)X110(W)X26(H) (725U) 125(L)X89(W)X30(H) (725U-M)		79(L)X110(W)X26(H) (725K) 125(L)X89(W)X30(H) (725K-M)	
重量(g)	270±10		270±10		150±10(725U) / 400±10(725U-M)		150±10(725K) / 400±10(725K-M)	

產品架構

